### **DATASHEET**

# FC Female to SC Female Hybrid Fiber adapter







### CINC (TITIL FC Female to SC Female Hybrid fiber adapter

#### Description

**Female to Female Hybrid Adapter** are developed to couple and mate two different (hybrid) connector plugs. The housing of the Adapters of the last generation has a reference key for the right position coupling and zirconia or phosphorus bronze split sleeve for high alignment.

This **FC(Female)** to **SC(Female)** SC footprint type fiber optic hybrid adapter, Converting FC connector to SC Connector. Variable FC interface conversion SC interface. Provided a simple and reliable solution for connecting two different optic fiber transmission joints.

#### Material

Parts name	Material	Color	
Housing body	Zinc alloy/PC/PEI	Metal/Blue/Green/Beige	
Sleeve	High precision Ceramic sleeve	White	
Dust Cover	ABS/Rubber	White/red/green/black	

#### Specification:

Test item	(SM-9/125) UPC	(SM-9/125) APC	MM PC			
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB			
Return Loss	≥50 dB	≥60 dB	≥35 dB			
Durability (500 Mating)	0.1dB Max.					
Withdrawal force(g/f)	200~600					
Storage Temp	-40 ~ +85					

#### **Products details**



Available

SM UPC, SM APC, MM OM1 62.5/125, MM OM2 50/125 MM OM3 50/125 MM OM4 50/125

Simplex-Sc footprint 1 metal

Simplex-Sc footprint Plastic



Simplex-Square



Duplex -Sc footprint



2.5mm High precision ceramic sleeve



## CMC Female to SC Female Hybrid fiber adapter

#### **Features**

Precision connection with sleeve SM and MM connector can be used interchangeably Low insertion loss, High Return loss Good interchangeability and reliability Meet IEC and ROHS standards High precision of mechanical dimensions Accuracy

#### **Applications**

Patch panels, ODF and other optical connections.

Optical networks demarcation and monitoring point

#### Order index

Products -	Fibers	- Fiber Mode	- Fiber Port -	- Adapter Shape	- Color
H2-Female to Female	1-Simplex	1- SM 9/125	A - FC/LC	1 - Standard	1 - metal
Fiber Adapter	2-Duplex	2- OM1 62.5/125	B - FC/SC	2 - SC footprint 1	2 - Blue
		3- OM2 50/125	C - FC/ST	3 - SC footprint 2	3 - Green
		4- OM3 50/125	D - LC/ST	4 - D hole	4 - Aqua
		5- OM4 50/125	E - LC/SC	5 - Square	5 - Beige
			F - SC/ST	6 - Rectangle	6 - meganta
			G - LC/E2000	7 - Rhombus	
			H - FC/E2000		
			I - DIN/FC		
			J - DIN/LC		
			K - DIN/SC		
			L - DIN/ST		
			M - SMA/SC		
			N - SMA/FC		
			O - SMA/ST		