# **DATASHEET**

# SC Female to LC Male conversion adapter







#### Description

**SC Female to LC male conversion adapter** adopt embedded optical fiber connector and optical fiber ferrule matching Sleeve joint technology. The products can hybrid a type of fiber optic connectors (male) into another type of optical fiber connector (male). It keeps the advantages of small size, light signal stable, easy to use characteristics, widely used in optical fiber equipment instrument testing and rescue project construction field.

This SC(Female) to LC(Male) fiber optic conversion adapter, Converting SC connector to LC Connector. Variable SC interface conversion LC interface. Provided a simple and reliable solution for connecting two different optic fiber transmission joints.

#### Specification:

Test item	(SM-9/125) UPC	(SM-9/125) APC	MM-50/125 PC	MM-62.5/125 PC						
Insertion Loss	≤0.3dB	≤0.3dB	≤0.3dB	≤0.3dB						
Return Loss	≥50 dB	≥60 dB	≥35 dB	≥35 dB						
Durability (500 Mating)	0.2dB Max.									
Operation Temp	-40 ~ +85									
Storage Temp	-40 ~ +85									

Remark: SC Female to LC Male Hybrid Adapter are ultra-reliable components featuring low insertion loss and back reflection loss. You can select single mode 9/125um or multimode 62.5/125um or multimode 50/125um.

#### **Products details**



## Available

SM UPC, SM APC, MM OM1 62.5/125, MM OM2 50/125 MM OM3 50/125 MM OM4 50/125

#### **Applications**


Telecom network

Optical data transmission connection

Fiber optic equipment testing and engineering rescue construction

#### **Features**

Low insertion loss High corrosion resistance High interface performance High return loss Easy to handle



### Order index

Products	-	Fibers	-	Fiber Mode	-	Female Connector	-	male Connector
I-Female to male		1-Simplex		1– SM 9/125		A– LC UPC		A– LC UPC
Fiber Adapter		2-Duplex		2- OM1 62.5/125		B- LC APC		B- LC APC
				3- OM2 50/125		C– SC UPC		C– SC UPC
				4– OM3 50/125		D- SC APC		D- SC APC
				5- OM4 50/125		E– FC UPC		E- FC UPC
						F– FC APC		F- FC APC
						G-ST UPC		G-ST UPC
						H- E2000 UPC		H- E2000 UPC
						I – E2000 APC		I – E2000 APC
						J- SMA UPC		J- SMA UPC